

USL 15/35 LED projector

APPLICATION:

Luminaire designed for universal installation on viewing windows, utilized in conjunction with a single light (single flange version) or on two distinct ports (double flange version).

Appropriate for glazing fittings:

- DIN 28120 / DIN 28121 (circulars)
- DIN 11851 (screw-on fitting)
- METAGLAS® and BioControl

Ideal for the chemical, pharmaceutical, food, and biogas sectors, encompassing bioreactors, laboratory mixers, filters, tanks, agitators, separators, and pipes.

TECHNICAL SPECIFICATIONS:

- Protection class: IP 65 (dust-tight and water jet-resistant) in accordance with EN 60529 / DIN VDE 0470
- Max. ambient temperature: 40°C
- Operating conditions: Not influenced by internal container pressure or vacuum.

⚠ Avoid direct exposure to the light (potential risk to vision)

CULINARY DELIGHT :

- Tension: 12 V, 24 V AC/DC
- 230 V AC
- Color temperature: 4000 K
 - Luminous flux: 210 lumens at 4.5 watts
 - 400 lm at 5.5 W
 - Reflected beam angle: 36° at 4.5 watts
 - 25° at 5.5 W

230V/24V AC transformers are available upon request.

INSTALLATION:

- USL 15-LED:
 - Securing the circular glazing flange or a flow indicator through an articulated support.
 - Grooved nut installation for screw-in glazing
- USL 35-LED:
 - Mounting through an adapter collar (for instance: attachment to Metaglas)
- The articulated bracket is included; however, the flange collar for DN 65 and above must be ordered separately.


NOMINAL DIMENSIONS:

- Circular glazing DIN 28120: starting from DN 40
- Circular glazing DIN 28121: starting from DN 40
- Visual flow indicators: starting from DN 40
- Screw-in glazing DIN 11851: starting from DN 65


<https://www.gallet-fr.com>



USL15



USL35



Components and materials:

- Luminaire housing and cover: Stainless steel 1.4404
- Articulated bracket and flange collar (for screw-on glazing DN 65): Stainless steel 1.4301
- Connection cable: 3 m (3 x 0.75 mm²) pre-installed (other lengths available upon request)
- Weight: 0.85 kg

Accessories:

- DN 65 stainless steel flange clamp (hinged bracket not required), diameter 80 mm
- DN 80 stainless steel flange clamp (no hinged bracket necessary), diameter 94 mm

Reference USL15	Reference USL35	Voltage	Watts	Press button	Time	Socket
Yes	/	12V	4W	without	Without	GU5.3
Yes	/	24V	4.5W	With	With	GU5.3
Yes	Yes	24V	4.5W	With	Without	GU5.3
Yes	Yes	24V	4.5W	without	Without	GU5.3
Yes	Yes	230V	5.5W	With	Without	GZ10
Yes	Yes	230V	5.5W	without	Without	GZ10
Yes	/	24V	4.5W	switch	Without	GU5.3
Yes	/	230V	5.5W	switch	Without	GZ10

<https://www.gallet-fr.com>